



# MSS®-TABNAK Crystal

## Crystallizer for natural stone floors containing calcium

### Features

All kinds of natural stone floors containing calcium become scrub-resistant, glossy, dirt-resistant, easy to clean and with a non-slip surface. The natural appearance and thus the characteristic patterns of different marble surfaces are impressively manifested. These excellent effects are the result of crystallization where the surface is densified without affecting the steam permeability of the stone slabs. The product has to be treated with a rotary floor machine and Litho-pads, using the spray cleaning method. Very economical to use. If used as described, it does not damage the environment. Contains more than 90%-biodegradable surfactants - well within legal requirements.

### Ingredients

Fluorosilicic acid > 10%, additives.

### Applications

Only suitable for natural stone floors containing calcium with polished surfaces such as Carrara marble, Solnhofen slabs, travertine and Jura. Please test beforehand if the product is suitable on marble quarry-artificial stone. Before crystallization, rough surfaces have to be polished with a machine.

Do not use on granite, quartz stone, sandstone, slate, nor on terrazzo, square concrete stone or ceramic stoneware.


### Directions

First thoroughly clean the stone surface and allow to dry. Shake well before use. Spray onto about 1 sq m of stone surface and immediately treat with machine (140-800 r.p.m.) using the Litho-pad. If the Litho-pad starts to grease, turn it over or replace it with a new one. The gleaming effect depends on the surface structure of the floor, therefore two or three applications may be necessary. In order to obtain a uniform gleaming effect the whole stone surface should finally be treated with a polish pad (red, beige or white) or a Litho-pad. After using, clean the head of the spray bottle with water.

### Security Symbols




### Floor Care



ISO 9001 : 2000  
ISO 14001 : 2004  
ISO 22000  
HACCP / TS 13001  
OHSAS 18001 / TS 18001



Sağlık Bakanlığı onaylıdır  
TSE (TSEK)  
Standartlarına göre üretilmiştir.



### CLEANINGCOLOUR CODE



C:Corrosive

R 22 Harmful if swallowed.  
R 34 Causes burns.  
R 52/53 Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

S 24/25 Avoid contact with skin and eyes.  
S 37 Wear suitable gloves.  
S 39 Wear eye/face protection.

**Product Code:** MSS11023

**Packaging:** 3 L (3,33 KG)

**Consumption per square metre:** First treatment: 5 ml

Successive treatment: 5 ml

Address: Ferhatpaşa Mahallesi Anadolu Caddesi No 14 Samandra İstanbul

Phone: 0090 216 660 08 98

Fax: 0090 216 660 08 99

E - Mail: [info@mssgrup.com](mailto:info@mssgrup.com)