

MSS®-TABNAK Emprex

Stone Rotector (All Natural Stones)



Features

MSS-Tabnak Emprex is an easy stone care product and thus a real alternative to stone crystallization. Stone surfaces protected with MSS-Tabnak Emprex provide a non-slip surface, are dirt-resistant and wipe-proof. By polishing with high-speed machine and Multi-Disc a highly glossy, durable and tread-proof surface protection is formed. If the gloss is diminished by constant wear in heavy traffic areas, affected parts of the coating can be restored using the spray method. Scuff marks can be easily removed by polishing with high-speed machine. Before recoating with MSS-Tabnak Emprex, only intensive cleaning without stripping is necessary. Expensive and time-consuming stripping does not have to be carried out. Contains more than 90% biodegradable surfactants - well within legal requirements.

Ingredients

Nonionic surfactants, waxes, polymers, additives.

Applications

Suitable for all absorbent natural and artificial stone such as marble, granite, square concrete stone and travertine.

Not suitable on porcelain tiles, ceramic floor tiles and highly polished stone surfaces.

Directions

First treatment on stripped stone surfaces


Apply MSS-Tabnak Emprex in small quantities (about 125-250 ml) on to the clean, dry stone surface and distribute immediately in a thin layer, with, for example, a flat mop. Apply undiluted on absorbent stone surfaces. On less absorbent stone surfaces apply diluted 1:1 in cold water. Depending on the absorbency level of the stone floor, 1-2 applications may be necessary at approx. 15-20 minutes intervals. For highly absorbent floors, a third application is recommended. Attention! If the coating is too thick, scuff marks may appear. Restoration of affected parts of coating

Apply MSS-Tabnak Emprex diluted 1:1 in cold water using the spray method.

Coating after intensive cleaning

Apply MSS-Tabnak Emprex undiluted or diluted 1:1 in cold water. Dry coating can be finish-polished with a high-speed polishing machine (800-1,600 r.p.m.) and a Multi-Disc, retaining both gloss and anti-slip properties.


Floor Care




ISO 9001 : 2000
ISO 14001 : 2004
ISO 22000
HACCP / TS 13001
OHSAS 18001 / TS 18001



Sağlık Bakanlığı onaylıdır
TSE (TSEK)
Standartlarına göre üretilmiştir.



CLEANING COLOUR CODE



Not Required
Hazard
Symbols

S 2 Keep out of the reach of children.

Product Code: MSS11033

Packaging: 3 L (3,06 KG)

Consumption per square metre: First treatment and basic maintenance: 12,5 - 25 ml per application
Coating after intensive cleaning: 12,5 - 25 ml per application

Adress: Ferhatpaşa Mahallesi Anadolu Caddesi No 14 Samandra İstanbul

Phone: 0090 216 660 08 98

Fax: 0090 216 660 08 99

E - Mail: info@mssgrup.com