



MSS®-TABNAK Polimer

Polymer Floor Polish

Features

Metal reticulated synthetic dispersion with high solids content and great coat building property with self-gleaming effect. Tabnak Polimer is a high quality basic care which is particularly durable, dirt-resistant, wipe-proof and provides a non-slip surface. Tabnak Polimer is resistant to disinfectant cleaners.

Ingredients

Synthetic coating, polyethylene hard wax, water soluble solvents, resins, plasticizer.

Applications

Suitable for water-resistant, stripped floor coverings, such as PVC, polyolefin, linoleum, absorbent natural and artificial stone, asphalt, etc.

Caution! Always check adhesion before using Tabnak Polimer on P-U or P-E floor coverings.

Directions

Distribute Tabnak Polimer undiluted in a thin layer on a clean floor. Depending on the absorbency level of the floor, 2-3 applications may be necessary at approx. 30 minute intervals.

Security Symbols




Floor Care




ISO 9001 : 2000
ISO 14001 : 2004
ISO 22000
HACCP / TS 13001
OHSAS 18001 / TS 18001



Sağlık Bakanlığı onaylıdır
TSE (TSEK)
Standartlarına göre üretilmiştir.



CLEANING COLOUR CODE



Not Required
Hazard
Symbols

R 52/53 Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
S 61 Avoid release to the environment. Refer to special instructions / Safety data sheets before use.

Product Code: MSS11013

Packaging: 3 L (3,09 KG)

Consumption per square metre: Coating: 25 ml per application

Address : Ferhatpaşa Mahallesi Anadolu Caddesi No 14 Samandra İstanbul / Türkiye

Phone: 0090 216 660 08 98

Fax: 0090 216 660 08 99

E - Mail: info@mssgroup.com