



MSS® -MOBİDİK Faller

Liquid Flocculant and Clarifier for Pools

Features

Settles particles in the water in pools, keeps them in the filter and cleans the pool water.

Composition: Contains polyaluminum chloride.

Usage and Amount

The solution should be prepared in a plastic container outside at 10% saturation and added to the water from different points of the pool.

In periodic use : 30 –40 gr. / for 10 m³ water (every 3–4 days)

In heavy pollution : 60 – 80 gr. / for 10 m³ water

The circulation pump should be operated during the dosing period and the system should be closed during sedimentation. The sediment should be collected at the bottom of the pool and then vacuumed. The pH value should be adjusted after the sedimentation process.


Storage

Stored in a cool and dry environment, away from direct sunlight, in its tightly closed original packaging. It should not be stacked more than two canisters on top of each other. Storage life is at least 1 year.

Safety Symbol




Havuz Bakımı



ISO 9001 : 2000
ISO 14001 : 2004
ISO 22000
HACCP / TS 13001
OHSAS 18001 / TS 18001



Sağlık Bakanlığı onaylıdır
TSE (TSEK)
Standartlarına göre üretilmiştir.



TEMİZLİK RENK KODU



Xi: Tahriş Edici

S 2 Çocukların ulaşabilecekları yerlerden uzak tutunuz.
S 26 Göz ile temasında su ile iyice yıkayın ve doktora başvurun.
S 28 Deri ile temasında derhal bol su ile iyice yıkayınız.

Product Code: MSS43017

Consumption Quantity:

Packaging Type: 20 L (20,64 KG)

Adres: Ferhatpaşa Mahallesi Anadolu Caddesi No 14 Ataşehir İstanbul

Telefon: (0216) 660 08 98

Fax: (0216) 660 08 99

E – Mail: info@mssgrup.com