


Application Method & pH



Risk Information



Safety Information



Quality Certificates



Application Areas



ABC- SS & Weldingshine

Weld Stain, Stainless Steel Cleaning and Maintenance Agent

Features

It is a special acidic product developed especially for cleaning processes of stainless steel and steel alloys. Thanks to the corrosion inhibitor in its content, the corrosive effect of acids on the metal is minimized. It removes corrosion deposits, layers formed by minerals, easily removes rust layers and heavy dirt. It removes welding stains.

Composition: Contains a special mixture of acids, surface active agents and complexing agent.

pH: 1 ± 1 **Specific gravity (g/cm³):** 1.2 ± 0.1

Areas of Use

SS & Weldingshine is safely used in cleaning stainless steel metal surfaces, removing rust layers and removing welding stains.

It is also used in cleaning mortar in cement silos, cleaning concrete residue in concrete pumps, mixers and steel construction scaffolding.

Usage Method

It is concentrated, depending on the density of the dirt, 1 unit Limecemex can be diluted with 5 units of water. After application on the surface, wait for 2-3 minutes, rub if necessary and rinse with clean water.

Use by Immersion Method:

The tank where the solution will be prepared must be fiberglass or plastic coated. Limecemex is diluted in the ratios specified above. The material whose surface will be prepared is left in the solution until it is cleaned. The cleaned material is rinsed with water and dried. The protective agent is applied immediately.

Storage

Do not store below 2 °C (35.6 °F) and above 50 °C (122 °F). Special precautions must be taken during storage and use. It is acidic! Shelf life is 4 years from the date of production.

Packaging

20 liters

Product code: TC 82057