


Application Method & pH



Risk Information



Safety Information



Quality Certificates



Application Areas



WBC- Carbograset

Powerful Carbon and Oil Remover

Features

Very concentrated. Economical. Non-flammable. Can be used hot or cold. Has a slight foaming feature. Over 90% biodegradable.

Composition: Contains alkali substances, silicates and surfactants.
pH (10% solution): 10 - 11 ± 1.0 **Specific gravity g/cm³:** 1.0 ± 0.1

Areas of Use

It removes all burnt oils, soot stains, oven blacks, tar and similar stains. It is an ideal product for exterior cleaning of buildings. It perfectly cleans oil layers formed by chimney smoke, soot, dirt, exhaust gases.

In the maritime sector, it is used in cleaning bilge tanks, fuel tanks and other cargo tanks of ships. It is used in cleaning winery sector equipment, food and agricultural machinery, poultry, meat industry equipment and oven pans. It is recommended to use it in cleaning the inner surface of boiler flame tubes.

How to Use

Carbograset is used hot or cold by spraying, brushing and dipping. Better results can be obtained when used hot. It is used diluted with 2% water in high-pressure sprayers and 20% water in hand spray or brush applications. It can be directly injected into tanks. Circulation should be done.

After applying Carbograset, wait 5-25 minutes for it to dissolve oil and carbon. If necessary, brush and rinse with plenty of water.

Boiler and Heater Cleaning: Better results are obtained when the environment to be cleaned is hot. After adding the material diluted with water up to 10%, turn on the heating for a while to loosen the dirt and rinse with plenty of water by circulating. It can cause oxidation on aluminum and zinc surfaces. Use by mixing with cold and 1/100 water and rinse with plenty of water.

Storage

Do not store below 2 °C (35.6 °F) and above 50 °C (122 °F). Shelf life is 4 years from the date of production.

Packaging

20 liters

Product code: TC 80067